

STANDARD FEATURES

- ➔ They protect stationary and mobile generator against the bad weather, against the theft and enables the reduction of the noise level.
- ➔ Enclosures are of 12 gauge steel. Steel sheet are electro zinc coated before painting (inside and outside) with a polyester powder rust inhibiting coat .
- ➔ High corrosion resistance: stainless covered with zinc, bolts and rivets, anodized aluminium alloy hinges flexible seals between body sections.
- ➔ Soundfoam between 20 and 50 mm (1 to 2 in) acoustical sound treatment
- ➔ Lifting eye(s) on top of the enclosure fixed to the skid
- ➔ Large doors allow easy access to the generator set for service and monitoring purposes
- ➔ Window in “securit” glass mounted on enclosure door for control viewing .
- ➔ A critical silencer is mounted inside the enclosure
- ➔ Emergency stop button is accessible from outside enclosure.



| Model | Sound level | | | Dimensions (mm) | Weight (kgs) | Tank (l) |
|-----------|-------------|----------|-----|--------------------|-----------------|-------------|
| | dB(A)@1m | dB(A)@7m | LWA | | | |
| V350U_208 | 86 | 76 | 105 | 4475 x 1410 x 2430 | 4170 | 470 |

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.