

**STANDARD FEATURES**

- ➔ They protect stationary and mobile generator against the bad weather, against the theft and enables the reduction of the noise level.
- ➔ Enclosures are of 12 gauge steel. Steel sheet are electro zinc coated before painting (inside and outside) with a polyester powder rust inhibiting coat .
- ➔ High corrosion resistance: stainless covered with zinc, bolts and rivets, anodized aluminium alloy hinges flexible seals between body sections.
- ➔ Soundfoam between 20 and 50 mm (1 to 2 in) acoustical sound treatment
- ➔ Lifting eye(s) on top of the enclosure fixed to the skid
- ➔ Large doors allow easy access to the generator set for service and monitoring purposes
- ➔ Window in “securit” glass mounted on enclosure door for control viewing .
- ➔ A critical silencer is mounted inside the enclosure
- ➔ Emergency stop button is accessible from outside enclosure.



| Model     | Sound level |          |     | Dimensions<br>(mm) | Weight<br>(kgs) | Tank<br>(l) |
|-----------|-------------|----------|-----|--------------------|-----------------|-------------|
|           | dB(A)@1m    | dB(A)@7m | LWA |                    |                 |             |
| D400U_208 | 89          | 79       |     | 5031 x 1560 x 2435 | 4256            | 500         |

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. \*ISO 8528.