

**M126**

Soundproofing canopy

STANDARD FEATURES

- ➔ They protect stationary and mobile generator against the bad weather, against the theft and enables the reduction of the noise level.
- ➔ Enclosures are of 12 gauge steel. Steel sheet are electro zinc coated before painting (inside and outside) with a polyester powder rust inhibiting coat .
- ➔ High corrosion resistance: stainless covered with zinc, bolts and rivets, anodized aluminium alloy hinges flexible seals between body sections.
- ➔ Soundfoam between 20 and 50 mm (1 to 2 in) acoustical sound treatment
- ➔ Lifting eye(s) on top of the enclosure fixed to the skid
- ➔ Large doors allow easy access to the generator set for service and monitoring purposes
- ➔ Window in "securit" glass mounted on enclosure door for control viewing .
- ➔ A residential silencer is mounted inside the enclosure
- ➔ Emergency stop button is accessible from outside enclosure.



Model	Sound level			Dimensions	Weight	Tank
	dB(A)@1m	dB(A)@7m	LWA	(mm)	(kg)	(L)
K20UM	77	67	92	1750 x 775 x 1230	700	50

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.

SDMO Industries - Headquarters / Siège social : 270 rue de Kerervern – 29490 Guipavas
SDMO Industries CS 40047 – 29801 Brest Cedex 9 – France
Tel. + 33 (0)2 98 41 41 41 Web: www.kohlersdmo.com